

Datenblatt Art. 396.181

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Kabeltrommel 4-fach

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Leitung bis max. 50m H05RR-F3G1,50mm ²		cable up to 50m H05RR-F3G1,50mm ²	
Stromausgang		Power output	
Steckdosen		Socket outlets	
4x CEE 7/3 (Type F)		4x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A / 250V~, IP20		16A / 250V~, IP20	
Schutzeinrichtungen		Protective devices	
Thermoschutzschalter	1-polig, rückstellbar	Thermo circuit breaker	1-pole, resettable
Scheibendurchmesser	280mm	Tabletop thickness	280mm
Lieferumfang	1x Kabeltrommel 4-fach ohne Deckel	Scope of delivery	1x cable reel 4-fold
Im Karton		In carton	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP20	Protection type	IP20

