

Datenblatt Art. 399.181

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Profi-Kabeltrommel 3-fach

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	25m H07RN-F 3G1,5mm ²	Supply cable	25m H07RN-F 3G1,5mm ²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	CEE 7/7 (Type E/F)	Plug	CEE 7/7 (Type E/F)
Stromausgang		Power output	
Steckdosen		Socket outlets	
3x CEE 7/3 (Type F)		3x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 35° mit Klappeckel		Black, similar to RAL 9005, 35° with cover	
16A / 250V~		16A / 250V~	
Schutzeinrichtungen		Protective devices	
Thermoschutzschalter	1-polig, rückstellbar	Thermo circuit breaker	1-pole, resettable
Weitere Produkteigenschaften		Further product attributes	
Abmessungen		Dimensions	
L/B/H	285/215/375mm	L/B/H	280/215/375mm
Durchmesser	285mm	disc diameter	285mm
Material		Material	
Gehäuse:		Housing:	
Trommelkörper aus bruchfestem Spezialkunststoff		PA6 GF30 850°C, black similar to RAL 9005, Reel body made from unbreakable special plastic	
Doppelrohrgestell		Dual tubular frame	
Lieferumfang		Scope of delivery	
1x Profi-Kabeltrommel 3-fach		1x Professional cable reel, 3-way	

Im Karton

In carton

Umgebungsbedingungen**Environmental conditions****Schutzart**

IP44

Protection type

IP44

Konformität / Approbation**Conformity / Approval****Bauart konform nach**

DGUV-I 203-006

Type approved

DGUV-I 203-006

