



Mechanical characteristics
cables

Mechanische Eigenschaften
Kabel

G 7: KX 22A; KX 3B; RG-174/U;
MRC 100 Flex (0.48L/1.5AF) Draka;
RG-188A/U; RG-316/U
RG-179B/U, RG-187A/U

assembly code
panel piercing

Montageanleitung
Montagebohrung

D0303
Z026

Components
body
crimp ferrule

Bauteile
Körper
Crimprohr

Materials / Material **Finish / Oberfläche**
CuZn39Pb3
Cu SF w
Cu1-2Ni-2Sn3-6 matt
Ni5

Electrical characteristics
impedance

Elektrische Eigenschaften
Wellenwiderstand

50 Ω

Environmental
RoHS compliant

Umgebung
RoHS konform

2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]		
			gez./ drawn	06.11.2019	MA			
			gepr./ appr	06.11.2019	BJ	ca./approx. 1		
			Maßstab/ scale 5:1 (1:1)	Benennung/ title Cable Terminator for PCB Kabeldirektanschluss für LTP				
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type K	Zeichnungsnr./ drawing no. H01000A0057			
			Ersatz für/ replaces				 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1	