

Mechanical characteristics
interface dimensions acc. to

Mechanische Eigenschaften
Steckgesicht nach

IEC 61169-8 (BNC)

Components
centre contact
outer contact
other metal parts
insulator

Bauteile
Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung

Materials / Material
brass / Messing
brass / Messing
brass / Messing
POM

Finish / Oberfläche
gold plated / vergoldet
nickel plated / vernickelt
nickel plated / vernickelt

Electrical characteristics
impedance
frequency
working voltage

Elektrische Eigenschaften
Wellenwiderstand
Frequenz
Betriebsspannung


50 Ω
0-2,5 GHz
max. 335 V

Environmental
operating temp.
RoHS compliant

Umgebung
Betriebstemperatur
RoHS konform

-40°C / +60°C
2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]		
			gez./ drawn	14.11.2019	MA			
			gepr./ appr.	22.11.2019	BJ	ca./approx.		
Maßstab/ scale 2:1 (1:1)				Benennung/ title BNC - Mini-UHF Adaptor (f-m) BNC - Mini-UHF-Kupplung (f-m)				
Untert./ doc. type K				Zeichnungsnr./ drawing no. J01008F0072			Maße/ dimensions: mm	
Ersatz für/ replaces							Original : DIN A4 Blatt/ sheet 1 von/ of 1	