


## Warm Schrumpfschlauch 2:1 - flexibel und farbig

### TF21 - dünnwandig

PRODUKTBEZEICHNUNG	Ø Liefermaß min. (D)	Größe (imperial)	Ø nach Schrumpfung max. (d)	Wanddicke (WT)
TF21-3.2/1.6-PO-X-RD	3,2	1/8 "	1,6	0,51
TF21-3.2/1.6-PO-X-WH	3,2	1/8 "	1,6	0,51
TF21-3.2/1.6-PO-X-BK	3,2	1/8 "	1,6	0,51
TF21-4.8/2.4-PO-X-BU	4,8	3/16 "	2,4	0,51
TF21-4.8/2.4-PO-X-YE	4,8	3/16 "	2,4	0,51
TF21-4.8/2.4-PO-X-RD	4,8	3/16 "	2,4	0,51
TF21-4.8/2.4-PO-X-WH	4,8	3/16 "	2,4	0,51
TF21-4.8/2.4-PO-X-OG	4,8	3/16 "	2,4	0,51
TF21-4.8/2.4-PO-X-BK	4,8	3/16 "	2,4	0,51
TF21-6.4/3.2-PO-X-BU	6,4	1/4 "	3,2	0,64
TF21-6.4/3.2-PO-X-YE	6,4	1/4 "	3,2	0,64
TF21-6.4/3.2-PO-X-RD	6,4	1/4 "	3,2	0,64
TF21-6.4/3.2-PO-X-WH	6,4	1/4 "	3,2	0,64
TF21-6.4/3.2-PO-X-BK	6,4	1/4 "	3,2	0,64
TF21-9.5/4.8-PO-X-BU	9,5	3/8 "	4,8	0,64
TF21-9.5/4.8-PO-X-YE	9,5	3/8 "	4,8	0,64
TF21-9.5/4.8-PO-X-OG	9,5	3/8 "	4,8	0,64
TF21-9.5/4.8-PO-X-RD	9,5	3/8 "	4,8	0,64
TF21-9.5/4.8-PO-X-WH	9,5	3/8 "	4,8	0,64
TF21-9.5/4.8-PO-X-BK	9,5	3/8 "	4,8	0,64
TF21-12.7/6.4-PO-X-BU	12,7	1/2 "	6,4	0,64
TF21-12.7/6.4-PO-X-YE	12,7	1/2 "	6,4	0,64
TF21-12.7/6.4-PO-X-RD	12,7	1/2 "	6,4	0,64
TF21-12.7/6.4-PO-X-WH	12,7	1/2 "	6,4	0,64
TF21-12.7/6.4-PO-X-BK	12,7	1/2 "	6,4	0,64
TF21-19.1/9.5-PO-X-OG	19,1	3/4 "	9,5	0,76
TF21-19.1/9.5-PO-X-BU	19,1	3/4 "	9,5	0,76
TF21-19.1/9.5-PO-X-YE	19,1	3/4 "	9,5	0,76
TF21-19.1/9.5-PO-X-RD	19,1	3/4 "	9,5	0,76
TF21-19.1/9.5-PO-X-BK	19,1	3/4 "	9,5	0,76
TF21-19.1/9.5-PO-X-WH	19,1	3/4 "	9,5	0,76
TF21-25.4/12.7-PO-X-BU	25,4	1 "	12,7	0,89
TF21-25.4/12.7-PO-X-YE	25,4	1 "	12,7	0,89
TF21-25.4/12.7-PO-X-RD	25,4	1 "	12,7	0,89
TF21-25.4/12.7-PO-X-BK	25,4	1 "	12,7	0,89
TF21-25.4/12.7-PO-X-WH	25,4	1 "	12,7	0,89
TF21-38.0/19.0-PO-X-BU	38,1	1-1/2 "	19,1	1,02
TF21-38.0/19.0-PO-X-YE	38,1	1-1/2 "	19,1	1,02
TF21-38.0/19.0-PO-X-RD	38,1	1-1/2 "	19,1	1,02
TF21-38.0/19.0-PO-X-BK	38,1	1-1/2 "	19,1	1,02
TF21-38.0/19.0-PO-X-WH	38,1	1-1/2 "	19,1	1,02

Alle Maße in mm. Technische Änderungen vorbehalten.





### Warm Schrumpfschlauch 2:1 - flexibel und farbig

TF21 - dünnwandig



Warm Schrumpfschlauch, Schrumpfrate: 2:1

PRODUKTBEZEICHNUNG	Ø Liefermaß min. (D)	Größe (imperial)	Ø nach Schrumpf max. (d)	Wanddicke (WT)
TF21-50.8/25.4-PO-X-BU	50,8	2 "	25,4	1,14
TF21-50.8/25.4-PO-X-YE	50,8	2 "	25,4	1,14
TF21-50.8/25.4-PO-X-RD	50,8	2 "	25,4	1,14
TF21-50.8/25.4-PO-X-BK	50,8	2 "	25,4	1,14
TF21-50.8/25.4-PO-X-WH	50,8	2 "	25,4	1,14
TF21-76.0/38.0-PO-X-BU	76,2	3 "	38,1	1,27
TF21-76.0/38.0-PO-X-YE	76,2	3 "	38,1	1,27
TF21-76.0/38.0-PO-X-RD	76,2	3 "	38,1	1,27
TF21-76.0/38.0-PO-X-BK	76,2	3 "	38,1	1,27
TF21-76.0/38.0-PO-X-WH	76,2	3 "	38,1	1,27
TF21-101.6/50.8-PO-X-BU	101,6	4 "	50,8	1,40
TF21-101.6/50.8-PO-X-YE	101,6	4 "	50,8	1,40
TF21-101.6/50.8-PO-X-RD	101,6	4 "	50,8	1,40
TF21-101.6/50.8-PO-X-BK	101,6	4 "	50,8	1,40
TF21-101.6/50.8-PO-X-WH	101,6	4 "	50,8	1,40

Alle Maße in mm. Technische Änderungen vorbehalten.