


CEE Box Steckdosenkombination 1xCEE 16 A+32 A  
FI40/0,03 A sowie 2xC16/1 und 1xC16/3**Leistungsmerkmale**

Die RED CEE Steckdosenkombination zur festen Wandmontage ist komplett montiert und anschlussfertig verdrahtet.

Die CEE BOX ist für das Weiterleiten und Verteilen von elektrischer Energie im Rahmen der Kenndaten gedacht. Die RED CEE BOX wurde zur Verwendung in Umgebungen bis zu einer Schutzart von IP54 konzipiert. Dank der professionellen Verdrahtung mit hochwertigen Schutzschaltgeräten können wir eine erhöhte Sicherheit gewährleisten. Die Schutzschaltgeräte mit Berührungsschutz nach DIN VDE 0106 Teil 100 sind unter einer transparenten und schlagfesten Makrolonabdeckung eingebaut. Die Steckdosen sind mit selbstabschließenden Klappdeckeln aus schlagfestem Polyamid 6 versehen. Alle außenliegenden Metallteile sowie Deckelschrauben sind nichtrostend. Alle Steckdosenkombinationen sind stückgeprüft und auf Wunsch liefern wir das entsprechende Prüfprotokoll. Das schlagfeste Gehäuse ist aus hochwertigem ABS-Kunststoff.

Die Schutzart ist IP54, die Temperaturbeständigkeit liegt bei -25 °C bis +40 °C.

**Technische Daten:**

Eingang über Anbauverschraubung M32 oben (Blindverschraubung M32 unten).

**Ausgang:**

1 CEE-Dose 32 A 400 V ungesichert,  
1 CEE-Dose 16 A 400 V 1xABB LS 16 A 3-pol C,  
4 Schuko-Dosen 230 V 2xABB LS 16 A 1-pol C,  
ABB FI 40 A 4-polig 0,03 A über alle Abgänge,  
Hauptleitungsabzweigklemme.

Maße (HxBxT): 369x204x130 mm.

Gewicht: 3,95 kg

**DEHA-Nummer**

6177977

**Artikelnummer**

3320-50-0001

**EAN**

4046725399841

**Kennzeichnung**IP  
54°C  
-25...+40

K2



## CEE Box Steckdosenkombination 1xCEE 16 A+32 A FI40/0,03 A sowie 2xC16/1 und 1xC16/3

### Technische Daten

Eingang:	über Anbauverschraubung M32 oben (Blindverschraubung M32 unten)
Ausgang:	1 CEE-Dose 32 A 400 V ungesichert, 1 CEE-Dose 16 A 400 V 1xABB LS 16 A 3-pol C, 4 Schuko-Dosen 230 V 2xABB LS 16 A 1-pol C, 1x ABB FI 40 A 4-polig 0,03 A über alle Abgänge, Hauptleitungsabzweigklemme
Maße (HxBxT):	369x204x130 mm
Gewicht:	3,95 kg
Farbe:	grau




### Bestelldaten

DEHA-Nummer	Typ	Art.-Nr.	EAN	VE
6177977	CEE BOX 3320-50-0001	3320-50-0001	4046725399841	1 St.

**RED**<sup>®</sup>

SIMPLY. CONVINCING.

CEE Box socket combination 1xCEE 16 A + 32 A  
FI40 / 0.03 A as well as 2xC16 / 1 and 1xC16 / 3

### Features

The RED CEE socket combination for fixed wall mounting is completely assembled and ready for connection.

The CEE BOX is for distributing of electrical energy within the framework of the characteristics. The RED CEE BOX is ready for use in environments up to a degree of protection of IP54.

Thanks to the professional wiring with high-quality circuit breakers we can ensure increased security. The circuit breakers with contact protection according to DIN VDE 0106 part 100 are installed under a transparent and impact-resistant makrolon-cover. The sockets are self-closing. Hinged lids are made of impact-resistant polyamide 6. All external metal parts and cover screws are rustproof. All socket outlet combinations are individually checked, and we deliver the corresponding test report on request.

The impact-resistant housing is made of high-quality ABS plastic. The protection class is IP54, the temperature resistance lies between -25 ° C and +40 ° C.

Technical specifications:

Input via screw connection M32 above (M32 blind screw connection below).

Output:

1 CEE socket 32 A 400 V -> unsecured,  
1 CEE socket 16 A 400 V 1xABB 1 LS 16 A 3-pin C,  
4 Schuko sockets 230 V 1xABB 2 LS 16 A 1-pole C,  
ABB FI 40 A 4-pole 0.03 A across all outlets,  
Main line branch terminal.

Dimensions (HxWxD): 369x204x130 mm.

Weight: 3.95 kg

Colour: grey

### DEHA number

6177977

### Item number

3320-50-0001

### EAN

4046725399841

### Identification

IP  
54°C  
-25...+40

K2



## CEE Box socket combination 1xCEE 16 A + 32 A FI40 / 0.03 A as well as 2xC16 / 1 and 1xC16 / 3

### General data

Input:	via screw connection M32 above (M32 blind screw connection below)
Output:	1 CEE-socket 32 A 400 V unsecured, 1 CEE-socket 16 A 400 V 1xABB LS 16 A 3-pin C, 4 Schuko sockets 230 V 2xABB LS 16 A 1-pin C, 1x ABB FI 40 A 4-polig 0,03 A across all outlets, Main line branch terminal
Dimensions (HxWxD):	369x204x130 mm
Weight:	3,95 kg
Colour:	grey



### Order data

DEHA-number	Type	Item-No.	EAN	VE
6177977	CEE BOX 3320-50-0001	3320-50-0001	4046725399841	1 pc.