



STEP ALU – Stromein- und Ausgang GST18	STEP ALU – Power in- and output GST18
LS-Leitungsschutzschalter: <ul style="list-style-type: none"> • 250V, 16A, • Auslösecharakteristik B • 2-polig 	Circuit breaker (CB): <ul style="list-style-type: none"> • 250V, 16A, • Tripping characteristic B • 2-pole
Anschluss: <ul style="list-style-type: none"> • Stromeingang: Stecker GST18 • Stromausgang: Buchse GST18 	Connection: <ul style="list-style-type: none"> • Power input: connector plug GST18 • Power output: connector coupling GST18
Profil: <ul style="list-style-type: none"> • Aluminium, eloxiert • Länge: 178mm 	Profile: <ul style="list-style-type: none"> • Aluminium, anodised • Length: 178mm
Abmessungen (LxBxH): <ul style="list-style-type: none"> • 220 x 52 x 44 mm 	Measurements (LxWxH): <ul style="list-style-type: none"> • 220 x 52 x 44 mm
Lieferform: <ul style="list-style-type: none"> • im Polybeutel 	Packaging: <ul style="list-style-type: none"> • in polybag
Lieferumfang: <ul style="list-style-type: none"> • 1 x STEP Steckdosenleiste 	Extent of delivery: <ul style="list-style-type: none"> • 1 x STEP power strip