



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX IBE 16.0010** Page 1 of 4 Certificate history:
Status: **Current** Issue No: 2 Issue 1 (2016-07-20)
Issue 0 (2016-03-10)
Date of Issue: 2020-05-08
Applicant: **Adolf Schuch GmbH, Lichttechnische Spezialfabrik**
Mainzer Straße 172
67547 Worms
Germany
Equipment: **LED linear luminaire type e 865* ***** and t 868* *******
Optional accessory:
Type of Protection: **Increased safety, encapsulation, powder filling, intrinsic safety, flameproof enclosure, protection by enclosure**
Marking: type e 865* ***** (depending on the components used)
Ex eb mb q IIC T4 Gb
Ex db eb mb q IIC T4 Gb
Ex eb ib mb q IIC T4 Gb
Ex db eb ib mb q IIC T4 Gb
Ex tb IIIC T80 °C Db

type t 868* *****
Ex tb IIIC T80 °C Db

Approved for issue on behalf of the IECEx
Certification Body:

Alexander Henker

Position:

Deputy Head of department Certification Body

Signature:
(for printed version)

Date:

2020-05-08

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

IBExU Institut für Sicherheitstechnik GmbH
Fuchsmühlenweg 7
09599 Freiberg
Germany



IECEX Certificate of Conformity

Certificate No.: **IECEX IBE 16.0010** Page 2 of 4

Date of issue: 2020-05-08 Issue No: 2

Manufacturer: **Adolf Schuch GmbH Lichttechnische Spezialfabrik**
Mainzer Straße 172
67547 Worms
Germany

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

IEC 60079-18:2017 Explosive atmospheres - Part 18: Protection by encapsulation "m"
Edition:4.1

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

IEC 60079-5:2015 Explosive atmospheres -Part 5: Equipment protection by powder filling "q"
Edition:4.0

IEC 60079-7:2017 Explosive atmospheres - Part 7: Equipment protection by increased safety "e"
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

DE/IBE/ExTR15.0002/00

DE/IBE/ExTR15.0002/01

DE/IBE/ExTR15.0002/02

Quality Assessment Report:

DE/PTB/QAR09.0004/05



IECEx Certificate of Conformity

Certificate No.: **IECEx IBE 16.0010**

Page 3 of 4

Date of issue: 2020-05-08

Issue No: 2

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The LED linear luminaire type e 865* ***** is used to illuminate factory shops and stores. It is suitable for the operation in hazardous areas of zone 1 and 21. Type t 868* ***** is exclusively intended for the use in zone 21.

The luminaire consists of the polyester enclosure with fasteners made of stainless steel, the reflector with the assembled LED boards, terminals and LED control gear as well as a light-transmitting cover made of polycarbonate.

The use of different internal components distinguishes type t 868 from e 865.

Technical data:

rated voltage:	220...250 V AC (50 / 60 Hz) or 176...275 V DC
input power:	up to 75 W
Through-wiring/looping:	up to 12 x $\geq 2.5 \text{ mm}^2$ (max. 4 x 16 A)
ambient temperature range:	-30 °C up to 70 °C

These values are maximum values. The actual values are determined by the built-in components. The manufacturer specified the rated values and ambient temperature range in the context of these limiting values and ensures compliance with the maximum surface temperature of the equipment and the permissible operating temperature of the components. The corresponding rated values / restrictions are indicated in the manufacturer's instructions.

SPECIFIC CONDITIONS OF USE: NO



IECEx Certificate of Conformity

Certificate No.: IECEx IBE 16.0010

Page 4 of 4

Date of issue: 2020-05-08

Issue No: 2

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

- The luminaire complies with the requirements of the current standards, thus the marking has been changed.
- A new type of enclosure has been added.