





Product features and key data

Applications	offices banks foyers sales rooms ticket halls exhibition rooms educational rooms
Luminaire type	Rectangular recessed LED luminaire with microprismatic cover P-WW.
Mounting method	Lay-in
Luminaire optic	The optical system consists of a highly efficient PMMA cover with microprisms. PWW (prismatic wallwasher).
Connected load	39 W
Power factor	0,95
Colour temperature	3.000 K
Rated luminous flux	4.900 lm
Luminous efficacy	125 lm/W
Interchangeability lightsource	Yes - interchangeable
Service life	L80 (25 °C) = 100.000 h L90 (25 °C) = 50.000 h
Colour rendering index	80
Colour tolerance	3 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body of extruded aluminium profile.
Electrical version	With external operating device, digitally dimmable (DALI).
DALI-2-Standard EN 62386	Yes
Connection method	Plug-in terminal
Touch-Dim-capable	Yes
Dimming range	1 - 100 %
Monitoring Ready	On request
Mains frequency	50/60 Hz
Mains voltage	220 - 240 V
Ingress Protection (IP) rating	IP20
Protection rating on room side	IP40
Protection class	II
Impact resistance (IK)	IK03
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	13
Max. Luminaires B16	20
Max. Luminaires C10	20
Max. Luminaires C16	34
Net length	1.246 mm
Net width	309 mm
Net height	22 mm
Recess length	1.246 mm
Recess width	309 mm
Recess depth	160 mm
Weight	3,6 kg

light distribution curve

**ArimoFit M57 P-WW 52-830
TX200084**

 DIN 5040: A50
 UTE: 1,00 C
 CEN Flux Code: 66 90 97 100 100

 C0 - C180
 C90 - C270

Available accessories

Material	Description
 ArimoFit M57 ZER 7574100	Recessing frame for plasterboard ceiling openings ArimoF M57...
 ArimoFit Kit EB3 round 7714550	Emergency light system for ceiling recessing with an emergency light operation time of 3 hours.
 ArimoFit Kit EB3 square 7714650	Emergency light system for ceiling recessing with an emergency light operation time of 3 hours.

Offer text

Rectangular recessed LED luminaire with microprismatic cover P-WW. Version M57 (312.5 mm x 1250 mm). Optionally, the luminaire can be equipped with an emergency light system for ceiling recessing with an emergency light operation time of 3 hours. In emergency light operation, the luminaire luminous flux is 500 lm. Generation of an enhanced depth effect in the room. For system ceilings with exposed grids. .. The Sky frame, optionally available as an accessory, creates a room-atmospheric depth effect in the classic, flat modular ceiling; the 3-dimensional contour of a skylight is reproduced. The optical system consists of a highly efficient PMMA cover with microprisms. PWW (prismatic wallwasher). The microstructured PMMA prism surface of the optical system has a glare-reducing effect, is non-yellowing and does not cloud. Harmonious light effect due to homogeneously illuminated light emission. Individual design of the light emission surface (e.g. with printing) and other special solutions are possible on request. connected load 39,00 W, connected load 39,00 W, luminous efficiency of luminaire 125 lm/W. Light colour warm white, correlated colour temperature (CCT) 3000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life $L_{80}(t_{q\ 25\ ^\circ\text{C}}) = 100,000$ h, mean rated service life $L_{90}(t_{q\ 25\ ^\circ\text{C}}) = 50,000$ h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Luminaire body of extruded aluminium profile. (RAL 9016). The narrow side profile is flush with the trunking. The luminaire frame is profiled in a 3-dimensional way to generate a depth effect on the ceiling. Luminaire can be covered with insulating material at $t_a\ 25^\circ\text{C}$, $t_a\ 35^\circ\text{C}$ without insulation material can be also be used. Safety class (EN 61140): II, protection rating (DIN EN 60529): IP20, Protection rating on room side: IP40, impact resistance level in accordance with IEC 62262: IK03, testing temperature of wire glow test in accordance with IEC 60695-2-11: $650\ ^\circ\text{C}$. Weight: 3,6 kg. Polarity-protected rapid connection with mains through-wiring up to $\varnothing\ 2.5\ \text{mm}^2$. Connection of the ballast unit to the luminaire (Plug 'N Play). The luminaire's packaging concept facilitates separate removal of the control gear unit for pre-assembly, leaving the remaining luminaire components protected until final assembly. With external operating device, digitally dimmable (DALI). Control gear unit according to DALI-2 standard (EN 62386). Luminaire is switchable and dimmable by means of touch functionality via DALI control terminals (Touch DIM). Control gear unit is open-circuit proof and protected against faulty connection, short circuit, overload and overtemperature. Output ripple of the control gear unit $\leq 4\%$ for effective control of the LED system and for flicker-free light. The luminaire can be equipped with the Monitoring Ready (MOR) functionality on request. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is part of a range of recessed, surface-mounted and suspended luminaires with a harmonised appearance. The application variety of the product series is underlined by variants regarding luminous flux packages, light distribution curves and protection ratings. On request, the basic range can be expanded with project-specific luminaire features.

EPREL ID

 D: 85401117
 D: LEDM+Kk ArimoF EA650-830-M57s L122W1