


Product features and key data

Applications	offices banks foyers sales rooms ticket halls exhibition rooms educational rooms
Luminaire type	Rectangular surface-mounted LED luminaire with microprismatic cover PW19.
Mounting method	Surface-mounting Suspension
Luminaire optic	The optical system consists of a highly efficient PMMA cover with microprisms.
Connected load	42 W
Power factor	0,95
Colour temperature	4.000 K
Rated luminous flux	5.300 lm
Luminous efficacy	126 lm/W
Interchangeability lightsource	Yes - interchangeable
Service life	L80 (25 °C) = 100.000 h L90 (25 °C) = 50.000 h
Colour rendering index	80
Colour tolerance	3 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	The surface-mounted luminaire consists of an installation body with connection unit, rapid plug connection and the control gear as well as a plug-on luminaire unit with LED-system, cover, rapid plug connection and frame.
Electrical version	With electronic transformer, digitally dimmable (DALI).
DALI-2-Standard EN 62386	Yes
Connection method	Plug-in terminal
Dimming range	1 - 100 %
Monitoring Ready	On request
Mains frequency	50/60 Hz
Mains voltage	220 - 240 V
Ingress Protection (IP) rating	IP20
Protection rating of lamp compartment	IP40
Protection class	I
Impact resistance (IK)	IK03
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	12
Max. Luminaires B16	20
Max. Luminaires C10	20
Max. Luminaires C16	34
Net length	1.557 mm
Net width	320 mm
Net height	42 mm
Weight	9,5 kg

light distribution curve


ArimoFit D3 PW19 53-840 LLWRR 01/01
TX150374

■ CD - C180
■ C90 - C270

UGR I = 18.1
UGR q = 18.0
DIN 5040: A50
UTE: 1,00 C
CEN Flux Code: 65 89 97 100 100 0 0 0 0

Available accessories

Material	Description
 ZAA/01 4601700	Ceiling rose, round. Colour white.
 ZAA/03 4601800	Ceiling rose, round. Colour silver-grey.
 ZAE/01 515 4691700	Ceiling rose, angular, white.
 ZAE/03 515 4691800	Ceiling rose for connection of the 5-pole mains cable in case of ceiling outlets. Square, silver-grey.
 ZAR/01 7002300	Ceiling rose, square, white.
 ZAR/03 7002400	Ceiling rose, square, silver grey.

Offer text

Rectangular surface-mounted LED luminaire with microprismatic cover PW19. For installation on ceilings and overhangs as well as horizontal wall installation indoors. The optical system consists of a highly efficient PMMA cover with microprisms. The microstructured PMMA prism surface of the optical system has a glare-reducing effect, is non-yellowing and does not cloud. With narrow-wide light distribution. Glare evaluation according to UGR rating (EN 12464-1) < 19. Suitable for VDU workstations according to EN 12464-1 via limited luminance $L \leq 3000 \text{ cd/m}^2$ for beam angle above 65° all-round.. Harmonious light effect due to homogeneously illuminated light emission. Individual design of the light emission surface (e.g. with printing) and other special solutions are possible on request. Luminaire luminous flux 5300 lm, connected load 42,00 W, luminous efficiency of luminaire 126 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life $L80(t_a 25^\circ\text{C}) = 100,000$ h, mean rated service life $L90(t_a 25^\circ\text{C}) = 50,000$ h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). The surface-mounted luminaire consists of an installation body with connection unit, rapid plug connection and the control gear as well as a plug-on luminaire unit with LED-system, cover, rapid plug connection and frame. Frame of extruded aluminium profile, colour white. Installation body of sheet steel, colour white. (RAL 9016). Dimensions (L x W): 1557 mm x 320 mm, height 42 mm. The frame is profiled in a 3-dimensional way. The undercut generates a shadow gap and reduces the perceived overall height. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, impact resistance level in accordance with IEC 62262: IK03, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 9,5 kg. The luminaire's packaging concept facilitates separate removal of the control gear unit for pre-assembly, leaving the remaining luminaire components protected until final assembly. With electronic transformer, digitally dimmable (DALI). Control gear unit according to DALI-2 standard (EN 62386). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). Control gear unit is open-circuit proof and protected against faulty connection, short circuit, overload and overtemperature. The luminaire can be equipped with the Monitoring Ready (MOR) functionality on request. With integrated LiveLink WiFi RC radio receiver for integration into a LiveLink WiFi RC mesh network and DALI interface for possible signal forwarding. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is part of a range of recessed, surface-mounted and suspended luminaires with a harmonised appearance. The application variety of the product series is underlined by variants regarding luminous flux packages, light distribution curves and protection ratings. On request, the basic range can be expanded with project-specific luminaire features.

Application note

In the case of horizontal wall installation, the closing springs must be aligned horizontally.

EPREL ID

D: LEDM+Kk ArimoF EA800-840-M59s L152W1