

## flush mounting socket outlet - housing dimensions 90x90





| Product description       |                              |
|---------------------------|------------------------------|
| BALS-Prd.-Nr              | 1410                         |
| EAN                       | 4024941222310                |
| Product category          | Flush mounting socket outlet |
| Current                   | 16A                          |
| Number of poles           | 3p                           |
| Arrangement of phases     | 2P+PE                        |
| Position of earth contact | 6 h                          |
| Voltage                   | 200 - 250V~                  |
| Frequency                 | 50/60Hz                      |

| Product description    |                                      |
|------------------------|--------------------------------------|
| Protection degree      | IP44                                 |
| Colour code            | blue RAL 5015                        |
| Colour of appliance    | white similar to RAL 9016            |
| Connection design      | with screw terminal                  |
| Maximum conductor size | 4,0 qmm                              |
| Cable entry            | other                                |
| Height                 | 115mm                                |
| Width                  | 105mm                                |
| Depth                  | 99mm                                 |
| Dimension of enclosure | 90x90 mm                             |
| Material of enclosure  | ABS + Polycarbonate                  |
| Contacts               | the contacts are brass nickel plated |

| Additional technical properties |  |
|---------------------------------|--|
|                                 | Architecture programme TH, hinged lid with labelling field (optional: key lock), flush mounting (incl. flush socket) |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.278 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941222310    |

| Logistics data |               |
|----------------|---------------|
| Length         | 99 mm         |
| Width          | 105 mm        |
| Height         | 115 mm        |
| Weight         | 0.279 kg      |
| Volume         | 2,224.404 ccm |
| Packaging      | Carton        |
| Content amount | 6 ST          |
| EAN            | 4024941222617 |
| Length         | 370 mm        |
| Width          | 218 mm        |
| Height         | 125 mm        |
| Weight         | 1.841 kg      |
| Volume         | 9,329.4 ccm   |



| Ampere Poles               | 16<br>3 | 16<br>4 | 16<br>5 | 32<br>5 | Schutzk.<br>Domestic |
|----------------------------|---------|---------|---------|---------|----------------------|
| a                          | 90,0    | 90,0    | 90,0    | 90,0    | 90,0                 |
| b                          | 90,0    | 90,0    | 90,0    | 90,0    | 90,0                 |
| c                          | 92,0    | 92,0    | 92,0    | 92,0    | 92,0                 |
| d                          | 115,0   | 115,0   | 115,0   | 115,0   | 115,0                |
| e                          | 64,0    | 64,0    | 64,0    | 64,0    | 64,0                 |
| f                          | 35,0    | 35,0    | 35,0    | 35,0    | 35,0                 |
| Cond. mm <sup>2</sup> min. | 1,0     | 1,0     | 1,0     | 2,5     | 1,0                  |
| Cond. mm <sup>2</sup> max. | 4,0     | 4,0     | 4,0     | 10      | 2,5                  |

4MB464

