

# phase sequence indicator - test plug with domestic-type socket





| Product description       |                                 |
|---------------------------|---------------------------------|
| BALS-Prd.-Nr              | 2234                            |
| EAN                       | 4024941022347                   |
| Product category          | Phase sequence indicator TRIPOL |
| Current                   | 16A                             |
| Number of poles           | 5p                              |
| Arrangement of phases     | 3p+N+PE                         |
| Position of earth contact | 6 h                             |
| Voltage                   | 200/346 - 240/415V~             |

| Product description            |         |
|--------------------------------|---------|
| Frequency                      | 50/60Hz |
| Protection degree              | IP44    |
| Display of the three phases    | TRUE    |
| Motor rotation direction test. | TRUE    |
| No-contact detection of direc. | TRUE    |
| Height                         | 155mm   |
| Width                          | 64mm    |
| Depth                          | 64mm    |

| Additional technical properties |   |
|---------------------------------|---|
|                                 | With integrated Schuko-type socket outlet 16A 230V AC German standard, Integrated electronic for: rotary field indicator connection of testing devices phase sequence indicator |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.24 kg / Piece |
| Packaging      | Bag             |
| Content amount | 1 ST            |
| EAN            | 4024941022347   |
| Length         | 64 mm           |
| Width          | 64 mm           |
| Height         | 155 mm          |
| Weight         | 0.241 kg        |

| Logistics data |               |
|----------------|---------------|
| Volume         | 634.88 ccm    |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941964524 |
| Length         | 245 mm        |
| Width          | 177 mm        |
| Height         | 185 mm        |
| Weight         | 2.533 kg      |
| Volume         | 7,140 ccm     |



| Ampere<br>Polzahl | 16<br>5 | 32<br>5 |
|-------------------|---------|---------|
| ø a               | 64,0    | 73,0    |
| b                 | 117,0   | 132,0   |
| x                 | 154,0   | 177,0   |
| y                 | 64,0    | 73,0    |
| z                 | 68,0    | 79,0    |
|                   |         |         |
|                   |         |         |
|                   |         |         |
|                   |         |         |