

plug - with TE screw terminals, for harsh applications



| Product description | |
|---------------------------|---------------|
| BALS-Prd.-Nr | 2181 |
| EAN | 4024941021814 |
| Product category | TE plug |
| Current | 63A |
| Number of poles | 3p |
| Arrangement of phases | 2P+PE |
| Position of earth contact | 6 h |
| Voltage | 200 - 250V~ |
| Frequency | 50/60Hz |

| Product description | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Protection degree | IP67 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Collar blue RAL 5015, Pusher black RAL 9005, Housing cover dark grey RAL 7012, Cable gland dark grey RAL 7012, Bajonet ring dark grey RAL 7012 |
| Connection design | screw terminal as box terminal |
| Maximum conductor size | 16,0 qmm |
| Cable entry | with cable gland |
| Height | 234mm |
| Width | 114mm |
| Depth | 114mm |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| | For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket and integrated strain relief |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.59 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941021814 |

| Logistics data | |
|----------------|---------------|
| Length | 114 mm |
| Width | 114 mm |
| Height | 234 mm |
| Weight | 0.591 kg |
| Volume | 3,041.064 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941964463 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 3.156 kg |
| Volume | 13,588.4 ccm |



| | 63 Polzahl 3 | 63 4 | 63 5 |
|---------------------------|--------------------|---------|---------|
| ø a | 114,0 | 114,0 | 114,0 |
| b | 153,0 | 153,0 | 153,0 |
| d | 171,0 | 171,0 | 171,0 |
| ø e | 36,0 | 36,0 | 36,0 |
| x | 233,0 | 233,0 | 233,0 |
| y | 114,0 | 114,0 | 114,0 |
| z | 114,0 | 114,0 | 114,0 |
| Cond. mm ² min | 6,0 | 6,0 | 6,0 |
| Cond. mm ² max | 16,0 | 16,0 | 16,0 |
| | | | |
| | | | |



