

panel mounting socket outlet, angled - flange 114x114,  
fixing centers 90x90



| Product description       |   |
|---------------------------|---|
| BALS-Prd.-Nr              | 12160                                   |
| EAN                       | 4024941121606                           |
| Product category          | TE panel mounting socket outlet, angled |
| Current                   | 63A                                     |
| Number of poles           | 5p                                      |
| Arrangement of phases     | 3p+N+PE                                 |
| Position of earth contact | 6 h                                     |
| Voltage                   | 200/346 - 240/415V~                     |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 50/60Hz  |
| Protection degree              | IP67   |
| Colour code                    | red RAL 3000   |
| Colour of appliance            | Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035                             |
| Connection design              | screw terminal as box terminal with Kontex-contact   |
| Maximum conductor size         | 25.0 qmm   |
| Cable entry                    | other  |
| Height                         | 125mm  |
| Width                          | 114mm  |
| Depth                          | 147mm  |
| Flange size vertical in mm     | 114mm  |
| Flange size horizontal in mm   | 114mm  |
| Drill hole dist. vertical mm   | 90mm   |
| Drill hole dist. horizontal mm | 90mm   |
| Material of enclosure          | Polyamide  |
| Contacts                       | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties |                        |
|---------------------------------|------------------------|
|                                 | The inclination is 15° |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.573 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941121606    |
| Length         | 147 mm           |
| Width          | 114 mm           |
| Height         | 125 mm           |
| Weight         | 0.574 kg         |
| Volume         | 2,094.75 ccm     |
| Packaging      | Carton           |
| Content amount | 5 ST             |
| EAN            | 4024941820448    |
| Length         | 295 mm           |
| Width          | 185 mm           |
| Height         | 215 mm           |
| Weight         | 3.029 kg         |
| Volume         | 9,975 ccm        |



| Ampere                     | 63    | 63    | 63    |  |  |  |
|----------------------------|-------|-------|-------|--|--|--|
| Polzahl                    | 3     | 4     | 5     |  |  |  |
| a                          | 114,0 | 114,0 | 114,0 |  |  |  |
| b                          | 114,0 | 114,0 | 114,0 |  |  |  |
| c                          | 90,0  | 90,0  | 90,0  |  |  |  |
| d                          | 90,0  | 90,0  | 90,0  |  |  |  |
| e $\varnothing$            | 6,5   | 6,5   | 6,5   |  |  |  |
| f                          | 12,0  | 12,0  | 12,0  |  |  |  |
| h                          | 65,0  | 65,0  | 65,0  |  |  |  |
| i                          | 80,0  | 80,0  | 80,0  |  |  |  |
| k                          | 92,0  | 92,0  | 92,0  |  |  |  |
| l                          | 92,0  | 92,0  | 92,0  |  |  |  |
| Leiter mm <sup>2</sup> min | 6     | 6     | 6     |  |  |  |
| Leiter mm <sup>2</sup> max | 25    | 25    | 25    |  |  |  |