

## Panel mounting socket outlet straight - flange 107x100 fixing centers 85x77



| Product description       |                                        |
|---------------------------|----------------------------------------|
| BALS-Prd.-Nr              | 13101                                  |
| EAN                       | 4024941131018                          |
| Product category          | Panel mounting socket outlet, straight |
| Current                   | 63A                                    |
| Number of poles           | 4p                                     |
| Arrangement of phases     | 3P+PE                                  |
| Position of earth contact | 7 h                                    |
| Voltage                   | 480 - 500V~                            |

| Product description            |                                                                                                          |
|--------------------------------|----------------------------------------------------------------------------------------------------------|
| Frequency                      | 50/60Hz                                                                                                  |
| Protection degree              | IP67                                                                                                     |
| Colour code                    | black RAL 9005                                                                                           |
| Colour of appliance            | Hinged lid black RAL 9005, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035                           |
| Connection design              | screw terminal as box terminal with Kontex-contact                                                       |
| Maximum conductor size         | 25.0 qmm                                                                                                 |
| Cable entry                    | other                                                                                                    |
| Height                         | 114mm                                                                                                    |
| Width                          | 111mm                                                                                                    |
| Depth                          | 133mm                                                                                                    |
| Flange size vertical in mm     | 107mm                                                                                                    |
| Flange size horizontal in mm   | 100mm                                                                                                    |
| Drill hole dist. vertical mm   | 85mm                                                                                                     |
| Drill hole dist. horizontal mm | 77mm                                                                                                     |
| Material of enclosure          | Polyamide                                                                                                |
| Contacts                       | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.55 kg / Piece |
| Packaging      | Bag             |

| Logistics data |               |
|----------------|---------------|
| Content amount | 1 ST          |
| EAN            | 4024941131018 |
| Length         | 133 mm        |
| Width          | 111 mm        |
| Height         | 114 mm        |
| Weight         | 0.551 kg      |
| Volume         | 1,682.982 ccm |
| Packaging      | Carton        |
| Content amount | 5 ST          |
| EAN            | 4024941958554 |
| Length         | 295 mm        |
| Width          | 185 mm        |
| Height         | 215 mm        |
| Weight         | 2.914 kg      |
| Volume         | 9,975 ccm     |



|                            | 63    | 63    | 63    |  |  |  |
|----------------------------|-------|-------|-------|--|--|--|
| Ampere                     | 63    | 63    | 63    |  |  |  |
| Polzahl                    | 3     | 4     | 5     |  |  |  |
| a                          | 107,0 | 107,0 | 107,0 |  |  |  |
| b                          | 100,0 | 100,0 | 100,0 |  |  |  |
| c                          | 85,0  | 85,0  | 85,0  |  |  |  |
| d                          | 77,0  | 77,0  | 77,0  |  |  |  |
| e ø                        | 6,5   | 6,5   | 6,5   |  |  |  |
| f                          | 12,0  | 12,0  | 12,0  |  |  |  |
| h                          | 56,5  | 56,5  | 56,5  |  |  |  |
| i                          | 76,0  | 76,0  | 76,0  |  |  |  |
| k                          | 113,0 | 113,0 | 113,0 |  |  |  |
| l ø                        | 88,0  | 88,0  | 88,0  |  |  |  |
| m                          | 7,0   | 7,0   | 7,0   |  |  |  |
| Leiter mm <sup>2</sup> min | 6     | 6     | 6     |  |  |  |
| Leiter mm <sup>2</sup> max | 25    | 25    | 25    |  |  |  |

4 MB 50