

plug - with screwless terminals



| Product description | |
|---------------------------|--------------------|
| BALS-Prd.-Nr | 2130 |
| EAN | 4024941021302 |
| Product category | QUICK-CONNECT plug |
| Current | 16A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 6 h |
| Voltage | 380 - 415V~ |
| Frequency | 50/60Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Collar red RAL 3000, Housing cover red RAL 3000, Cable gland grey RAL 7035 |
| Connection design | screwless spring-clamp technology |
| Maximum conductor size | 2,5 qmm |
| Cable entry | with cable gland |
| Height | 146mm |
| Width | 60mm |
| Depth | 65mm |
| Material of enclosure | Polyamide |
| Contacts | The contacts are brass, The contact carrier is made of polyamide |

| Additional technical properties | |
|---------------------------------|---|
| | Screwless housing connection with snap fastening, For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket and integrated strain relief |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.146 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941021302 |

| Logistics data | |
|----------------|---------------|
| Length | 65 mm |
| Width | 60 mm |
| Height | 146 mm |
| Weight | 0.147 kg |
| Volume | 569.4 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941958042 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.585 kg |
| Volume | 5,737.5 ccm |

