

panel mounting socket outlet, straight - flange 75x75,
fixing centers 60x60



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 13336 |
| EAN | 4024941133364 |
| Product category | TE panel mounting socket outlet QUICK-CONNECT, straight |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 - 240/415V~ |

| Product description | |
|--------------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Enclosure grey RAL 7035 |
| Connection design | screwless spring terminals with Kontex-Kontakt |
| Maximum conductor size | 4,0 qmm |
| Cable entry | other |
| Height | 86mm |
| Width | 75mm |
| Depth | 93mm |
| Flange size vertical in mm | 75mm |
| Flange size horizontal in mm | 75mm |
| Drill hole dist. vertical mm | 60mm |
| Drill hole dist. horizontal mm | 60mm |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.149 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941133364 |
| Length | 93 mm |
| Width | 75 mm |
| Height | 86 mm |
| Weight | 0.15 kg |
| Volume | 599.85 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941828062 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.615 kg |
| Volume | 5,737.5 ccm |

