


## plug - with screwless terminals, for harsh applications



Product description	
BALS-Prd.-Nr	21484
EAN	4024941214841
Product category	QUICK-CONNECT TE plug
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	10 h
Voltage	> 50V~
Frequency	100 - 300Hz

Product description	
Protection degree	IP67
Colour code	green RAL 6002
Colour of appliance	Cable gland grey RAL 7035, Collar green RAL 6002, Housing cover green RAL 6002, Bayonet ring grey RAL 7035
Connection design	screwless spring-clamp technology
Maximum conductor size	6,0 qmm
Cable entry	with cable gland
Height	182mm
Width	102mm
Depth	102mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings, For cable diameter from 13 up to max. 27 mm

Logistics data	
Weight/pcs	0.348 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941214841

Logistics data	
Length	102 mm
Width	102 mm
Height	182 mm
Weight	0.349 kg
Volume	1,893.528 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941822268
Length	330 mm
Width	216 mm
Height	260 mm
Weight	3.706 kg
Volume	17,062.5 ccm

