

## wall mounting appliance inlet - with hinged cover



Product description	
BALS-Prd.-Nr	24415
EAN	4024941244152
Product category	TE wall mounting appliance inlet Quick-Connect
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~
Frequency	50/60Hz

Product description	
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Housing bottom grey RAL 7035, Housing top grey RAL 7035, Collar red RAL 3000, Hinged lid grey RAL 7035
Connection design	screwless spring-clamp technology
Maximum conductor size	6,0 qmm
Cable entry	top entry M25
Height	148mm
Width	90mm
Depth	118mm
Dimension of enclosure	75x90 mm (HxW)
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	The cable entry is one at top open and one rear sided closed
	With hinged lid

Logistics data	
Weight/pcs	0.351 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941244152
Length	118 mm
Width	90 mm
Height	148 mm
Weight	0.352 kg
Volume	1,571.76 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941822961
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.716 kg
Volume	13,588.4 ccm

