


hanging connector - with MULTI-GRIP, with suspension clip




Product description	
BALS-Prd.-Nr	3221
EAN	4024941032216
Product category	QUICK-CONNECT TE hanging connector
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Cable gland grey RAL 7035, Enclosure red RAL 3000
Connection design	screwless spring terminals with Kontex-Kontakt
Maximum conductor size	6,0 qmm
Cable entry	with cable gland
Height	212mm
Width	72mm
Depth	99mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 13 up to max. 27 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.391 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941032216
Length	99 mm
Width	72 mm
Height	212 mm
Weight	0.392 kg
Volume	1,511.136 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941970068
Length	325 mm
Width	217 mm
Height	210 mm
Weight	4.116 kg
Volume	13,588.4 ccm

	Ampere	16	16	16	32	32	32
	Polzahl	3	4	5	3	4	5
a Ø	51,0	58,0	65,0	66,5	66,5	72,0	
b	156,0	162,0	168,0	195,0	195,0	198,0	
c	72,0	78,0	86,0	89,0	89,0	99,0	
d Ø	18,0	18,0	21,0	23,0	23,0	27,0	
e Ø	39,5	39,5	35,5	48,5	48,5	44,5	
h	167,5	173,5	171,5	208,0	208,0	205,0	
Leiter mm² min	1	1	1	2,5	2,5	2,5	
Leiter mm² max	2,5	2,5	2,5	6	6	6	