

GGM INOX V4A (PG)



20.093.031_a

MAT

V4A / 1.4404 / AISI 316L
X2RCrNiMo17-12-2

TEMP

-50°C bis +250°C
-50°C à +250°C
-50°C to +250°C




NORM

DIN 60423

Sechskantmutter GGM INOX V4A
Aus Edelstahl rostfrei.

Contre-écrou GGM INOX V4A
En acier inoxydable.

Locknut GGM INOX V4A
Stainless steel.

	A mm			Plica-Nr.	E-Nr.	VE
PG7	2.9	15	V4A	92.6001.070	126 359 000	50
PG9	2.9	19	V4A	92.6001.091	126 359 001	50
PG11	3.1	21	V4A	92.6001.111	126 359 002	50
PG13.5	3.1	23	V4A	92.6001.133	126 359 003	50
PG16	3.1	26	V4A	92.6001.163	126 359 004	50
PG21	3.6	32	V4A	92.6001.214	126 359 005	50
PG29	4.1	42	V4A	92.6001.297	126 359 006	50
PG36	5.1	57	V4A	92.6001.362	126 359 007	50
PG42	5.1	60	V4A	92.6001.420	126 359 008	25
PG48	5.6	65	V4A	92.6001.480	126 359 009	25