

LED-recessed spot
Artikel-Nr. 12411073



LED-Einbaudownlight, weiß, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 590lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: No. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12411073		
Stand:	19.07.2021 11:35		
Colour of light	3000 K	Outer diameter	100 mm
Colour	White	Built-in diameter	82 mm
Beam angle	40 °	Installation depth	65 mm
Amount of light sources / fittings	1 Qty	Current	350 mA
Material	Aluminium	Luminous flux	590 lm
Lamp holder	Plug&Play	Degree of protection	IP20
Power	6,2 W	Protection class	III
Lamp	LED	Adjustability	Not adjustable
Colour rendering	CRI > 80	Circuit type	Series conduction