



Recessed ceiling spot
Article no. 01-72079



Tender	
Recessed ceiling spot, gold, Round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: GZ4, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 35 W, Adjustability: Not adjustable, without control gear, Type of dimming: Depending on driver.	

Article data	
Article no.	01-72079
GTIN	4250047732297
Short description	Recessed ceiling spot
Colour	gold
Shape	Round
Outer diameter	64 mm
Built-in diameter min.	42 mm
Built-in diameter max.	47 mm
Installation depth	45 mm
Weight	0.041 kg
D licence plate	No
Conformance	CE, UKCA


Recessed ceiling spot

Article no. 01-72079

Operating technology of the luminaire	
System output	50 W
Voltage type	AC/DC
AC nominal voltage max	12 V
Frequency max	50 Hz
Lamp	LV halogen lamp
Lamp holder	GZ4
Protection class	III
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material
Material cover	Other

Packing data	
Gross weight	0.055 kg
Length of packaging	85 mm
Packaging width	85 mm
Packaging height	45 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.