



Recessed wall light
Article no. 10003013



Tender
Recessed wall light, Rectangular. Ceiling cut-out L x W 70 x 90 mm, Installation depth 50 mm, Length 87 mm, Width 120 mm, Weight 0,265 kg, Cover Other Power 1 x 3 W, Light colour warm white, Correlated color temprature (CCT) 3.200 K, Colour rendering index CRI > 80, Housing material: Brass / Steel, Colour: brass, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Article data	
Article no.	10003013
GTIN	4250047764953
Short description	Recessed wall light
Material	Brass / Steel
Colour	brass
Shape	Rectangular
Length	87 mm
Width	120 mm
Built-in length	70 mm
Built-in width	90 mm
Installation depth	50 mm
Hight	1.5 mm
Weight	0.265 kg
Conformance	CE, UKCA


Recessed wall light
 Article no. 10003013

Lighting technology	
Colour temperature	3.200 K
Light colour	white
System efficiency	3 lm/W
Colour rendering	CRI > 80
Operating technology of the luminaire	
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	III
Degree of protection	IP20
Dimmable	Yes
Control	Depending on driver
Energy efficiency class	not required
Mounting technology	
Mounting method	Recessed mounting
Place of installation	Wall-mounted
Further references	No cover with thermal insulation material
Material cover	Other
Packing data	
Gross weight	0.294 kg
Length of packaging	130 mm
Packaging width	130 mm
Packaging height	55 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.