



Recessed ceiling spot
Article no. 12041073



Tender
Recessed ceiling spot. Ceiling cut-out Ø 68 mm, Installation depth 60 mm, Length 82 mm, Width 82 mm, Weight 0,207 kg, with rotations-symmetrical, deep, wide distributed light intensity. Power 9 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index , Housing material: Aluminium, Colour: white, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Article data	
Article no.	12041073
GTIN	4250047768333
Short description	Recessed ceiling spot
Material	Aluminium
Colour	white
Type of surface	Matt
Length	82 mm
Width	82 mm
Built-in diameter min.	68 mm
Built-in diameter max.	68 mm
Installation depth	60 mm
Hight	66 mm
Weight	0.207 kg
D licence plate	No
Conformance	CE, UKCA


Recessed ceiling spot

Article no. 12041073

Lighting technology	
Colour temperature	3.000 K
Light colour	white
System efficiency	9 lm/W
Beam angle	38°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	9 W
Current	700 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	III
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	25°
Further references	No cover with thermal insulation material

Packing data	
Gross weight	0.23 kg
Length of packaging	105 mm
Packaging width	90 mm
Packaging height	75 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.