



Recessed ceiling spot
Article no. 12272023



Tender
Recessed ceiling spot, Square. Ceiling cut-out Ø 95 mm, Installation depth 60 mm, Length 110 mm, Width 110 mm, Weight 0,29 kg, with rotationssymmetrical, deep, wide distributed light intensity. Power 14 W, Light colour warm white, Correlated color temperature (CCT) 2.700 K, Colour rendering index , , Colour: chrome, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Article data	
Article no.	12272023
GTIN	4250047792444
Short description	Recessed ceiling spot
Colour	chrome
Type of surface	Glossy
Shape	Square
Length	110 mm
Width	110 mm
Built-in diameter min.	95 mm
Built-in diameter max.	95 mm
Installation depth	60 mm
Weight	0.29 kg
D licence plate	No
Conformance	CE, UKCA


Recessed ceiling spot

Article no. 12272023

Lighting technology	
Colour temperature	2.700 K
System efficiency	14 lm/W
Reflector	High-gloss
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
Current	700 mA
Lamp	LED
Lamp holder	Without fitting
Protection class	III
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted

Packing data	
Gross weight	0.375 kg
Length of packaging	140 mm
Packaging width	115 mm
Packaging height	120 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.