


LED-recessed spot
Artikel-Nr. 12032023



LED-Einbaudownlight, chrom, square. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP54, Protection class: (EN 61140) III, Current: 350 mA, Power: 1.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 70lm, Colour temperature: 3100 K, Light colour : White, Beam angle: 15°, Adjustability: Not adjustable, With control gear: No. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12032023
Stand:	20.07.2021 16:14

Colour of light	3100 K
Colour	Chrome
Length	39 mm
Beam angle	15 °
Amount of light sources / fittings	1 Qty
Material	Aluminium
Lamp holder	Plug&Play
Power	1,2 W
Lamp	LED
Colour rendering	CRI > 80
Built-in diameter	28 mm

Installation depth	24 mm
Current	350 mA
Luminous flux	70 lm
Degree of protection	IP54
Protection class	III
Adjustability	Not adjustable
Length	39 mm
Width	39 mm
Height	8 mm
Circuit type	Series conduction