


LED-Anbaustrahler
Artikel-Nr. 88527073



LED-Anbaustrahler, mehrfarbig, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 29.5W, Luminous flux: 2.669lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 40°, Adjustability: Rotatable and adjustable head, With control gear: Yes, control: on/off. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr. 88527073
Stand: 21.07.2021 23:34

Colour of light	3000 K
Colour	Multi-coloured
Beam angle	40 °
Material	Aluminium
Power	29,5 W
Lamp	LED
Colour rendering	CRI > 80
control	on/off
Outer diameter	127 mm
Voltage	230V AC 50Hz

Luminous flux	2,669 lm
Degree of protection	IP20
Protection class	I
Adjustability	Rotatable and adjustable head
Height	107 mm
Rotation angle	355 °
Swivel angle	90 °
Head adjustable angle	180 °
Circuit type	Parallel conduction
Suitable for through-wiring	No