


LED-Anbaustrahler  
**Artikel-Nr. 88528073**



LED-Anbaustrahler, mehrfarbig, square. Surface mounting, Ceiling-mounted. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 29,5W, Luminous flux: 2.669lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 40°, Adjustability: Rotatable and adjustable head, With operating gear, Type of dimming: switchable, . This luminaire contains incorporated and non-exchangeable LED light sources.

**Artikel-Nr.** 88528073  
**Stand:** 11.02.2021 18:51

colour of light	3000
Colour	multi-coloured
length	130 mm
Radiation angle	40 °
material	Aluminium
Power	29,5 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	switchable
voltage	230V AC 50Hz
Luminous flux	2,669 lm

IP protection class	IP20
Protection class	I
Adjustability	Rotatable and adjustable head
length	130 mm
Width	130 mm
Height	107 mm
Swivel angle	90 °
Head adjustable angle	180 °
circuit type secondary side	parallel conduction
Suitable for through-wiring	No