

LED recessed spot
Artikel-Nr. 12069553



recessed spot, mehrfarbig, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Luminous flux: 410lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 20°, Adjustability: Rotable and pivoted, With control gear: No. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12069553
Stand:	20.07.2021 08:13

Colour of light	3000 K
Colour	Multi-coloured
Beam angle	20 °
Material	Aluminium
Lamp holder	Plug&Play
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Outer diameter	100 mm
Built-in diameter	86 mm

Installation depth	50 mm
Current	350 mA
Luminous flux	410 lm
Degree of protection	IP20
Protection class	III
Adjustability	Rotable and pivoted
Height	25 mm
Rotation angle	355 °
Swivel angle	80 °
Circuit type	Series conduction