


LED-Tracklight

Artikel-Nr. 88381173

LED-Schienenstrahler, strukturweiß. Surface mounting, Ceiling-mounted. Inkl. Lichtquelle: 1 x LED COB, Systemleistung: 31,3 W, Wärmeableitung: passiv (ohne Lüfter), Rotationswinkel: dreh- / schwenkbar, Maße Leuchte: Ø 110 mm x 225 mm, Leuchte inkl. Euro-Adapter für Standard-3-Phasen-Schienen, inkl. Betriebsgerät, schaltbar, Leistungsfaktor > 0,9 (230 V AC 50 Hz), Gewicht: 1,5 kg. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 31.3W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.574lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 38°, Adjustability: Rotatable and adjustable head, With control gear: Yes, control: on/off.

Artikel-Nr.	88381173
Stand:	22.07.2021 03:47

Beam angle	38 °
Colour of light	3000 K
Colour	strukturweiß
Luminous flux	2,574 lm
System efficiency	82 lm/W
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Power	30 W
Lamp	LED
Colour rendering	CRI > 80
control	on/off
Outer diameter	110 mm

Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Rotatable and adjustable head
Length	253 mm
Width	110 mm
Height	225 mm
Rotation angle	355 °
Swivel angle	90 °
Head adjustable angle	90 °
Circuit type	Parallel conduction
Suitable for through-wiring	No