


LED surface mounted downlight

Artikel-Nr. 12060174



LED surface mounted downlight, white, round. Surface mounting, Ceiling-mounted. LED surface-mounted downlight (on/off switchable) with slightly decentralized light emission opening as a design element. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 8W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 640lm, Colour temperature: 4000K, Light colour : White, Beam angle: 120°, With control gear: Yes, Type of dimming: on/off. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12060174
Stand:	18.06.2021 16:30

Colour of light	4000 K
Colour	White
Beam angle	90 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	8 W
Lamp	High voltage LED
Colour rendering	CRI > 80

Type of dimming	on/off
Outer diameter	140 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Height	50 mm
Circuit type	Parallel conduction