


## LED-Schienenstrahler

**Artikel-Nr. 88381174**

LED-Schienenstrahler, strukturweiß. Surface mounting, Ceiling-mounted. Inkl. Lichtquelle: 1 x LED COB, Systemleistung: 31,3 W, Wärmeableitung: passiv (ohne Lüfter), Rotationswinkel: dreh- / schwenkbar, Maße Leuchte: Ø 110 mm x 225 mm, Leuchte inkl. Euro-Adapter für Standard-3-Phasen-Schienen, inkl. Betriebsgerät, schaltbar, Leistungsfaktor > 0,9 (230 V AC 50 Hz), Gewicht: 1,5 kg. Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 31,3W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 2.833lm, Farbtemperatur: 4000K, Colour of light: white, Radiation angle: 38°, Adjustability: Rotatable and adjustable head, With operating gear, Type of dimming: switchable, .

<b>Artikel-Nr.</b>	<b>88381174</b>
<b>Stand:</b>	11.02.2021 20:00

Radiation angle	38 °
colour of light	4000
Colour	strukturweiß
Luminous flux	2,833 lm
system efficiency	91 lm/W
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
Power	30 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	switchable

Outer diameter	110 mm
voltage	230V AC 50Hz
IP protection class	IP20
Protection class	I
Adjustability	Rotatable and adjustable head
length	253 mm
Width	110 mm
Height	225 mm
Swivel angle	90 °
Head adjustable angle	90 °
circuit type secondary side	parallel conduction
Suitable for through-wiring	No