


LED-Tracklight

Artikel-Nr. 88381184

LED-Schienenstrahler, strukturschwarz. Surface mounting, Ceiling-mounted. Inkl. Lichtquelle: 1 x LED COB, Systemleistung: 31,3 W, Wärmeableitung: passiv (ohne Lüfter), Rotationswinkel: dreh- / schwenkbar, Maße Leuchte: Ø 110 mm x 225 mm, Leuchte inkl. Euro-Adapter für Standard-3-Phasen-Schienen, inkl. Betriebs-gerät, schaltbar, Leistungsfaktor > 0,9 (230 V AC 50 Hz), Gewicht: 1,5 kg. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 31.3W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.833lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 38°, Adjustability: Rotatable and adjustable head, With control gear: Yes, control: on/off.

Artikel-Nr. 88381184
Stand: 22.07.2021 03:35

| | |
|------------------------------------|-------------------|
| Beam angle | 38 ° |
| Colour of light | 4000 K |
| Colour | strukturschwarz |
| Luminous flux | 2,833 lm |
| System efficiency | 91 lm/W |
| Beam angle | 38 ° |
| Amount of light sources / fittings | 1 Qty |
| Material | Aluminium / Glass |
| Power | 30 W |
| Lamp | LED |
| Colour rendering | CRI > 80 |
| control | on/off |
| Outer diameter | 110 mm |

| | |
|-----------------------------|-------------------------------|
| Voltage | 230V AC 50Hz |
| Degree of protection | IP20 |
| Protection class | I |
| Adjustability | Rotatable and adjustable head |
| Length | 253 mm |
| Width | 110 mm |
| Height | 225 mm |
| Rotation angle | 355 ° |
| Swivel angle | 90 ° |
| Head adjustable angle | 90 ° |
| Circuit type | Parallel conduction |
| Suitable for through-wiring | No |