


LED converter 700mA, ZigBee dimmable
Artikel-Nr. 17771000



LED converter 700mA, ZigBee dimmable, This driver fulfills the requirements for safety lighting systems in accordance with DIN EN 50172 VDE 0108-100:2005-01. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 700 mA, Voltage: 230V AC 50Hz, Power: 36W, dimmable: Yes, Control: Zigbee.

Artikel-Nr.	17771000
Stand:	06.12.2021 15:48

version	Plug&Play
Power	7-36 W
Current	700 mA
Output power	7-36 W
Control	Zigbee
Material	Plastic
Environment temperature (ta)	-25 °C bis +45 °C
Measure point (tc)	max. +80 °C
Power	7-36 W
Dimensions	L 146,5 x B 44 x H 30 mm
Input voltage	AC: 220-240 V, DC: 198-276 V

scope of delivery	Plug&Play version with 110 mm P&P output cable
Voltage	230V AC 50Hz
Current	700 mA
Circuit type	Series conduction
Degree of protection	IP20
Protection class	II
Voltage type	DC
Length	146.5 mm
Width	44 mm
Aufbauhöhe	30 mm