

Surface mounted housing square, flush, with module bracket recessed, pivoted



Surface mounted housing square, flush, with module bracket recessed, pivoted, white, square. Surface mounting, Ceiling-mounted. All Brumberg MR16 LED modules can be used for the surface mounted unit M1 up to the specified power. The LED module, the converter or the power supply unit and, if applicable, the control are not included in the scope of delivery of the surface mounted unit. We will be happy to answer any questions you may have about the selection of converters that fit into the housing. Important: when using 24 V LED modules, the power supply unit and the control must always be installed on site outside the housing. Lamp holder: Without fitting, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 8W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Pivoted, With control gear: No, Control: Other.

Artikel-Nr.	45112170
Stand:	07.12.2021 09:45

Colour	White
Length	90 mm
Amount of light sources / fittings	1 Qty
Control	Other
Width	90 mm
Material	Aluminium
Aufbauhöhe	115 mm
Lamp holder	Without fitting
Power	LED, max. 8 W

Lamp	Other
scope of delivery	Incl. module holder recessed, pivoted
Length	90 mm
Degree of protection	IP20
Protection class	III
Swivel angle	20 °
Circlip	Without circlip
Adjustability	Pivoted