

Surface mounted housing rechteckig, flush, with module brackets recessed, pivoted



Surface mounted housing rechteckig, flush, with module brackets recessed, pivoted, white, rectangular. Surface mounting, Ceiling-mounted. All Brumberg MR16 LED modules can be used for the surface mounted unit M1 up to the specified power. The LED module, the converter or the power supply unit and, if applicable, the control are not included in the scope of delivery of the surface mounted unit. We will be happy to answer any questions you may have about the selection of converters that fit into the housing. Important: when using 24 V LED modules, the power supply unit and the control must always be installed on site outside the housing. Lamp holder: Without fitting, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 8W, Amount of light sources / fittings: 2.0 Qty, Adjustability: Pivoted, With control gear: No, Control: Other.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 45125170         |
| Stand:      | 07.12.2021 10:19 |

|                                    |                   |
|------------------------------------|-------------------|
| Colour                             | White             |
| Amount of light sources / fittings | 2 Qty             |
| Control                            | Other             |
| Width                              | 92 mm             |
| Material                           | Aluminium         |
| Aufbauhöhe                         | 95 mm             |
| Lamp holder                        | Without fitting   |
| Power                              | 2 x LED, max. 8 W |
| Lamp                               | Other             |

|                      |                                          |
|----------------------|------------------------------------------|
| scope of delivery    | Incl. module brackets, recessed, pivoted |
| Length               | 173 mm                                   |
| Degree of protection | IP20                                     |
| Protection class     | III                                      |
| Swivel angle         | 20 °                                     |
| Circlip              | Without circlip                          |
| Adjustability        | Pivoted                                  |