

Recessed housing, rectangular, flush, 2-x, with flush module holders, rigid
Artikel-Nr. 45024170



Recessed housing, rectangular, flush, 2-x, with flush module holders, rigid, white, rectangular. In a compact design, for installation in tool-less rapid assembly systems. All Brumberg MR16 LED modules can be used for the installation unit M1 up to the maximum specified power. The installation depth of the luminaire depends on the LED module used. The LED module is not included in the scope of delivery of the installation unit. Lamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 14W, Amount of light sources / fittings: 2.0 Qty, With control gear: No, control: Other.

Artikel-Nr. 45024170			
Stand: 19.07.2021 19:17			
Colour	White	control	Other
Length	175 mm	Built-in width	160 mm
Amount of light sources / fittings	2 Qty	Built-in length	81 mm
Material	Aluminium	Degree of protection	IP20
Lamp holder	Without fitting	Protection class	III
Power	2 x LED, max. 14 W	Circlip	Without circlip
Lamp	Other	Length	175 mm
Shipping	Incl. module brackets flush, rigid, IP44	Width	92 mm
		Height	2.5 mm

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.