


LED system recessed spot COUPLED, dim2warm

Artikel-Nr. 12644073

LED system recessed spot COUPLED, dim2warm, white, square. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Installation is only with plaster or installation frame 82040170, 82041170, 82042170 or 82043170 possible. . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 500 mA, Power: 9.4W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 920lm, Colour temperature: from 1.800 K up to 3.000 K, Beam angle: 34°, Adjustability: Rotable and pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr. 12644073
Stand: 25.10.2021 21:41

Colour temperature	3000 K - 1800 K
Colour	White
Length	68 mm
Beam angle	34 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	9,4 W
Lamp	LED
Colour rendering	CRI > 90
Control	Dimming depending on driver
Installation depth	96 mm

Current	500 mA
Luminous flux	920 lm
Degree of protection	IP20
Protection class	III
Adjustability	Rotable and pivoted
Length	68 mm
Width	68 mm
Rotation angle	350 °
Swivel angle	20 °
Circuit type	Series conduction