

Surface mounted housing rechteckig, flush, with module brackets flush, rigid
Artikel-Nr. 45 124 170



Surface mounted housing rechteckig, flush, with module brackets flush, rigid , white, rectangular. Surface mounting, Ceiling-mounted. All Brumberg MR16 LED modules can be used for the surface mounted unit M1 up to the specified power. The LED module, the converter or the power supply unit and, if applicable, the control are not included in the scope of delivery of the surface mounted unit. We will be happy to answer any questions you may have about the selection of converters that fit into the housing. Important: when using 24 V LED modules, the power supply unit and the control must always be installed on site outside the housing. Lamp holder: Without fitting, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 8W, Amount of light sources / fittings: 2.0 Qty, With control gear: No, Control: Other.

Artikel-Nr.	45 124 170
Stand:	07.12.2021 10:45

Colour	White
Amount of light sources / fittings	2 Qty
Control	Other
Width	92 mm
Material	Aluminium
Aufbauhöhe	95 mm
Lamp holder	Without fitting
Power	2 x LED, max. 8 W

Lamp	Other
scope of delivery	Incl. module brackets flush, rigid, IP44
Length	173 mm
Degree of protection	IP20
Protection class	III
Circlip	Without circlip