


Spotlight LED recessed downlight 3000K/4000K/5700K
Artikel-Nr. 32026073



Spotlight LED recessed downlight 3000K/4000K/5700K, white, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Plastic, Degree of protection: according to DIN EN 60529 IP54*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 10W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 700lm, Colour temperature: from 3000 K up to 5700 K, Beam angle: 90°, Adjustability: Not adjustable, With control gear: Yes.

Artikel-Nr.	32026073
Stand:	19.07.2021 10:23

Colour	White	Built-in diameter	90 mm
Beam angle	90 °	Installation depth	84 mm
Amount of light sources / fittings	1 Qty	Voltage	230V AC 50Hz
Material	Plastic	Luminous flux	700 lm
Lamp holder	Without fitting	Impact resistance	IK03
Power	10 W	Degree of protection	IP54*
Lamp	LED	Protection class	II
Colour rendering	CRI > 80	Adjustability	Not adjustable
Outer diameter	115 mm	Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.