

Recessed housing oval, flush, 2-x, recessed with module holders, pivoted
Artikel-Nr. 45022170



Recessed housing oval, flush, 2-x, recessed with module holders, pivoted, white, other. In a compact design, for installation in tool-less rapid assembly systems. All Brumberg MR16 LED modules can be used for the installation unit M1 up to the maximum specified power. The installation depth of the luminaire depends on the LED module used. The LED module is not included in the scope of delivery of the installation unit. Installation diameter: 2x82 mm Lamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 14W, Amount of light sources / fittings: 2.0 Qty, With control gear: No, control: Other.

Artikel-Nr.	45022170
Stand:	20.07.2021 11:13

Colour	White
Length	175 mm
Amount of light sources / fittings	2 Qty
Material	Aluminium
Lamp holder	Without fitting
Power	2 x LED, max. 14 W
Lamp	Other
Shipping	Incl. module brackets, recessed, pivoted
control	Other

Built-in width	164 mm
Built-in length	82 mm
Degree of protection	IP20
Protection class	III
Circlip	Without circlip
Length	175 mm
Width	92 mm
Height	2.5 mm
Swivel angle	20 °