


LED recessed downlight, TunableWhite
Artikel-Nr. 12423074



LED recessed downlight, TunableWhite, white, round. In a compact design, for installation in tool-less rapid assembly systems
Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 24V, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 460lm, Colour temperature: from 2.700 K up to 6.000 K, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12423074		
Stand:	25.10.2021 20:03		
Colour temperature	2700 K - 6000 K		
Colour	White		
Beam angle	120 °		
Amount of light sources / fittings	1 Qty		
Material	Aluminium / Plastic		
Power	7* W		
Lamp	LED		
Colour rendering	CRI > 80		
Control	Dimming depending on driver		
Outer diameter	120 mm		
Built-in diameter	105 mm		
Installation depth	60 mm		
Voltage	24V		
Degree of protection	IP20		
Protection class	III		
Adjustability	Not adjustable		
Circuit type	Parallel conduction		