


LED converter 500 mA, trailing-edge phase dimmable

Artikel-Nr. 17822010



LED converter 500 mA, trailing-edge phase dimmable, This driver fulfills the requirements for safety lighting systems in accordance with DIN EN 50172 VDE 0108-100:2005-01. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 2.5 mm². . Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 500 mA, Voltage: 230V AC 50Hz, Power: 20W, Control: Trailing-edge phase.

Artikel-Nr.	17822010
Stand:	14.12.2021 12:03

version	ohne
Power	8-20 W
Current	500 mA
Control	Trailing-edge phase
Material	Plastic
Environment temperature (ta)	-25 °C bis +45 °C
Measure point (tc)	max. +75 °C
Power	8-20 W
Dimensions	L 110,5 x B 52 x H 22 mm
Input voltage	AC: 220-240 V

Voltage	230V AC 50Hz
Current	500 mA
Circuit type	Series conduction
Degree of protection	IP20
Protection class	II
Voltage type	AC
Length	110.5 mm
Width	52 mm
Aufbauhöhe	22 mm