


LED converter 350 mA, on/off
Artikel-Nr. 17621000



LED converter 350 mA, on/off, This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 21W, Control: on/off.

Artikel-Nr.	17621000
Stand:	06.12.2021 16:02

version	Plug&Play
Power	1-21 W
Current	350 mA
Control	on/off
Material	Plastic
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. +85 °C
Power	1-21 W
Dimensions	L 128 x B 50 x H 13 mm
Input voltage	AC: 220-240 V

scope of delivery	Plug&Play version with 110 mm P&P output cable
Voltage	230V AC 50Hz
Current	350 mA
Circuit type	Series conduction
Degree of protection	IP20
Protection class	II
Length	128 mm
Width	50 mm
Aufbauhöhe	13 mm

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.