


LED converter 350 mA, DALI dimmable (digital)
Artikel-Nr. 17683000



LED converter 350 mA, DALI dimmable (digital), This driver fulfills the requirements for safety lighting systems in accordance with DIN EN 50172 VDE 0108-100:2005-01. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 0.75-1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz , Power: 17W, Control: DALI-2 .

Artikel-Nr.	17683000
Stand:	06.12.2021 18:20

version	Plug&Play
Power	3,5-17 W
Current	350 mA
Control	DALI-2
Material	Plastic
Enviroment temprature (ta)	-25 °C bis +45 °C
Measure point (tc)	max. +75 °C
Power	3,5 - 17 W
Dimensions	L 110,5 x B 52 x H 22 mm
Input voltage	AC: 110-240 V, DC: 176-280 V
scope of delivery	Plug&Play version with 110 mm P&P output cable

Voltage	230V AC 50Hz
Current	350 mA
Circuit type	Series conduction
Degree of protection	IP20
Protection class	II
Voltage type	DC
Length	110.5 mm
Width	52 mm
Aufbauhöhe	22 mm