


LED recessed downlight
Artikel-Nr. 12090073



LED recessed downlight, white, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 3W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 300lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12090073
Stand:	25.10.2021 20:20

Colour temperature	3000 K
Colour	White
Beam angle	120 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Lamp holder	Plug&Play
Power	3 W
Lamp	LED
Colour rendering	CRI > 80

Control	Dimming depending on driver
Outer diameter	68 mm
Built-in diameter	60 mm
Installation depth	16.5 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Circuit type	Series conduction