


QualityFlex Special Applications, OneCut, CRI > 90, 18 W / m, IP00, 12 V DC
Artikel-Nr. 15311027



QualityFlex Special Applications, OneCut, CRI > 90, 18 W / m, IP00, 12 V DC, white, 2.700K, CRI > 90. LED flex lighting for decorative, technical as well as efficient lighting of light coves, linear applications and backlighting, basic or general lighting of rooms, architectural applications and for areas where high illumination is required, such as indirect or direct lighting, luminous ceilings, gastronomy lighting and much more. Länge: 5000.0 mm Lampenleistung je Meter: 18.0 W/m, Lichtstrom je Meter: 1470.0 lm/m, Schutzart raumseitig: IP00, Schutzklasse: III, Spannung: 12V DC, Abstrahlwinkel: 120.0 °, 72 LEDs pro Meter, Chip-Abstand (Short Pitch) : 13,89mm. Zur Individuellen Anwendung kann die LED-Flexplatine alle 13,89 mm eingekürzt werden. Die maximale Systemlänge von 5.000mm darf mit einer Einspeisung nicht überschritten werden. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	15311027
Stand:	06.12.2021 17:54

Colour temperature	2700 K
Light colour	White
Luminous flux per meter	1,470 lm/m
Power	90 W
Lamp power per meter	18 W/m
Beam angle	120 °
Length	5,000 mm
Width	12 mm
Aufbauhöhe	2.2 mm
Length of individual sections	13.89 mm
Degree of protection	IP00

Protection class	III
McAdam-Step	McAdam-Step 3
Short Pitch	13.89 mm
Number of lamps per meter	72 Qty
Voltage	12V
Voltage type	DC
Ambient temperature	-10 °C bis +40 °C
Control	Dimming depending on driver
Circuit type	Parallel conduction
Length of the connection line	350 mm
Maximum module length	5,000 mm