


Ceiling recessed speaker, DA 68 mm

**Artikel-Nr. 43004070**



Ceiling recessed speaker, DA 68 mm, white. In a compact design, for installation in tool-less rapid assembly systems. Nominal / music load capacity: 3 / 4 W, impedance: 20 Ohm. Up to 5 speakers can be connected in parallel to a channel of a HiFi amplifier. Sound pressure level: 1 W / 1 m: 82 dB (at nominal output of 87 dB), Transmission range (-3 db): 200 - 16,000 Hz, Transmission range (-10 db): 150 - 20,000 Hz, Net weight: 0.1 kg. Connection using 2-core cable with connecting terminals. Also available with cover in champagne matte or black on request. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel, Degree of protection: according to DIN EN 60529 IP20, Adjustability: Pivoted.

**Artikel-Nr.** 43004070  
**Stand:** 06.12.2021 10:45

|                      |                   |
|----------------------|-------------------|
| Colour               | White             |
| Material             | Aluminium / Steel |
| Built-in diameter    | 68 mm             |
| Installation depth   | 35 mm             |
| Degree of protection | IP20              |

|               |                 |
|---------------|-----------------|
| Circlip       | Without circlip |
| Adjustability | Pivoted         |
| Length        | 82 mm           |
| Width         | 82 mm           |
| Swivel angle  | 25 °            |