


LED converter 350 mA, trailing-edge phase dimmable

Artikel-Nr. 17640010



LED converter 350 mA, trailing-edge phase dimmable, This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 2.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 10W, Control: Trailing-edge phase.

| | |
|--------------------|------------------|
| Artikel-Nr. | 17640010 |
| Stand: | 06.12.2021 16:49 |

| | |
|------------------------------|---------------------------------------------------|
| version | ohne |
| Power | 4,2-10 W |
| Current | 350 mA |
| Control | Trailing-edge phase |
| Material | Plastic |
| Environment temperature (ta) | -25 °C bis +45 °C |
| Measure point (tc) | max. +70 °C |
| Power | 4,2-10 W |
| Dimensions | L 102 x B 38 x H 21 mm |
| Input voltage | AC: 220-240 V |
| scope of delivery | Plug&Play version with 110 mm P&P output cable |

| | |
|----------------------|-------------------|
| Voltage | 230V AC 50Hz |
| Current | 350 mA |
| Circuit type | Series conduction |
| Degree of protection | IP20 |
| Protection class | II |
| Voltage type | DC |
| Length | 102 mm |
| Width | 38 mm |
| Aufbauhöhe | 21 mm |